

**Nenninhalt: 4 000 Liter**    Tankdurchmesser: 1 600 mm    Gesamtlänge: 2 270 mm    Gefälle: 1%

cm	Liter	cm	Liter	cm	Liter	cm	Liter	cm	Liter	cm	Liter
1	3	31	549	61	1421	91	2384	121	3293	151	3960
2	9	32	575	62	1452	92	2416	122	3320	152	3974
3	16	33	601	63	1484	93	2448	123	3348	153	3987
4	25	34	628	64	1515	94	2480	124	3375	154	3999
<b>5</b>	<b>36</b>	<b>35</b>	<b>654</b>	<b>65</b>	<b>1547</b>	<b>95</b>	<b>2512</b>	<b>125</b>	<b>3401</b>	<b>155</b>	<b>4010</b>
6	47	36	681	66	1579	96	2543	126	3428	156	4020
7	60	37	708	67	1611	97	2575	127	3454	157	4028
8	74	38	736	68	1643	98	2606	128	3480	158	4035
9	88	39	763	69	1675	99	2638	129	3505	159	4036
<b>10</b>	<b>103</b>	<b>40</b>	<b>791</b>	<b>70</b>	<b>1707</b>	<b>100</b>	<b>2669</b>	<b>130</b>	<b>3531</b>	<b>160</b>	<b>4036</b>
11	119	41	819	71	1739	101	2700	131	3555		
12	136	42	848	72	1771	102	2732	132	3580		
13	153	43	876	73	1803	103	2762	133	3604		
14	171	44	905	74	1836	104	2793	134	3628		
<b>15</b>	<b>189</b>	<b>45</b>	<b>934</b>	<b>75</b>	<b>1868</b>	<b>105</b>	<b>2824</b>	<b>135</b>	<b>3651</b>		
16	208	46	963	76	1900	106	2855	136	3674		
17	228	47	993	77	1932	107	2885	137	3697		
18	248	48	1022	78	1965	108	2915	138	3719		
19	269	49	1052	79	1997	109	2946	139	3741		
<b>20</b>	<b>290</b>	<b>50</b>	<b>1082</b>	<b>80</b>	<b>2029</b>	<b>110</b>	<b>2976</b>	<b>140</b>	<b>3762</b>		
21	312	51	1112	81	2062	111	3005	141	3783		
22	334	52	1142	82	2094	112	3035	142	3803		
23	356	53	1173	83	2126	113	3065	143	3823		
24	379	54	1203	84	2159	114	3094	144	3843		
<b>25</b>	<b>402</b>	<b>55</b>	<b>1234</b>	<b>85</b>	<b>2191</b>	<b>115</b>	<b>3123</b>	<b>145</b>	<b>3861</b>		
26	426	56	1265	86	2223	116	3152	146	3879		
27	450	57	1296	87	2256	117	3180	147	3897		
28	474	58	1327	88	2288	118	3209	148	3914		
29	499	59	1358	89	2320	119	3237	149	3930		
<b>30</b>	<b>524</b>	<b>60</b>	<b>1389</b>	<b>90</b>	<b>2352</b>	<b>120</b>	<b>3265</b>	<b>150</b>	<b>3946</b>		

Tabellenzahlen rechnerisch ermittelt, für amtliche Zwecke nicht geeignet. Aufgrund der üblichen Toleranzen und der unterschiedlichen Einbaubedingungen sind Abweichungen bis zu 6% möglich.